



PA5X140

ULTRA HIGH POWER
ONE-PIECE PA SYSTEM
POWERED MONITOR

POUND FOR POUND *THE WORLD'S MOST POWERFUL PA SYSTEM*

Never before has so much power been packed into a complete sound system that's smaller than a shoe box and weighs only 13 pounds. The CORE PA5X140 produces a ground shaking 146 watts (at 4 ohms), enough to power its internal speaker and two Galaxy Audio HOT SPOT Personal Monitors. Its 114 dB maximum sound pressure level is louder than most systems many times its size. It features a ¼-inch input, an XLR input, a three band equalizer, and one of Galaxy's legendary ferro fluid cooled five-inch drivers with

a 40-ounce magnet structure. A frequency response of 200 Hz to 18 kHz and 98 dB (1 watt/1 meter)

sensitivity ensure that the PA5X140 delivers incredible intelligibility and superior gain before feedback and can cut through the most extreme ambient noise levels. Its cabinet is constructed of

black, fire-retardant styrene with a black

cast aluminum faceplate/grille. An integral adaptor allows the PA5X140 to be

mounted on a microphone stand. Positioned in close proximity to the performer, the PA5X140 is louder, more direct, and less likely to cause feedback than a conventional floor monitor. And as a one-piece PA system nothing else its

size and weight can approach its power and volume. When plugged into Galaxy Audio's FAR OUTLET™ personal power source the PA5X140 is fully portable. It even comes with a handle. The PA5X140 is made in the U.S.A..



PA5X140

ULTRA HIGH POWER
ONE-PIECE PA SYSTEM
POWERED MONITOR



SPECIFICATIONS

AMPLIFIER SECTION

Power Output: 100 watts @ 8 ohms (typically 146 watts @ 4 ohms).

Distortion: 8 ohm <0.05% THD 4 Ohm <0.1% THD

Minimum Recommended Load Impedance: 4 ohms

Frequency response: 200 Hz–20 kHz

Equalization: Three band center detent

Lo: ± 12 dB peak/dip at 300 Hz

Mid: ± 12 dB peak/dip at 2 kHz

Hi: ± 12 dB peak/dip at 10 kHz

Input connections (each with individual volume control):

One ¼-inch, balanced

One XLR, balanced, with +24 VDC phantom power

Output connections:

One ¼-inch speaker level for minimum 8 ohm load.

One (post-EQ, post-level) RCA line out



 **FerroSound**

SPEAKER SECTION

Speaker: One Galaxy Audio S5C160-8 ferro fluid cooled 5-inch driver with 40 oz. (1.1kg) magnet structure

Nominal impedance: 8 ohms

Power handling capacity: 100 watts @ 8 ohms

Sensitivity (1 Watt @ 1 meter): 98 dB (1 kHz octave band)

Frequency response: 200 Hz–18 kHz

Maximum SPL @ clip (100 Watts @ 1 meter): 114 dB

Sploft: 9.12

Enclosure Materials: Fire retardant styrene

Color: Black case with black cast aluminum grille

Dimensions: 6.75" x 10.94" x 6" (171 mm x 278 mm x 152 mm)

Net weight: 12.5 lbs. (5.7 kg)

Shipping weight: 13.5 lbs. (6.1 kg)

ARCHITECT AND ENGINEER SPECIFICATIONS

The PA system shall be a portable integrated unit featuring an amplifier, two-channel mono mixer with phantom power, equalizer, compressor and a single loudspeaker. The amplifier shall be capable of producing 146 continuous watts of power to a 4 ohm load, 100 watts of continuous power to the internal 8 ohm speaker. The mixer section shall include one balanced (differential) input using a ¼-inch phone plug connector and one +24 VDC phantom powered balanced (differential) input using an XLR connector. The mixer section shall include two separate sensitivity controls capable of automatically adjusting the gain to handle line, instrument or mic level inputs and a RCA connector capable of line level output. Equalization shall be accomplished via a three band equalizer: ± 12 dB shelving at 300 Hz, ± 12 dB peak/dip at 3 kHz, ± 12 dB shelving at 10 kHz. The PA system shall have a ¼-inch speaker level output jack capable of driving an 8 ohm load. The internal loudspeaker shall be a ferro fluid cooled 5-inch full range driver with a 40 ounce magnet structure. Sensitivity measured at 1 watt at 1 meter (1 kHz, octave band) shall be 98 dB. The enclosure shall be constructed of fire retardant styrene with fade-resistant colors. The cabinet finish shall be black with a black cast aluminum bezel. Dimensions shall be 6 inches (152 mm) high, 10.94 inches (278 mm) wide and 6.75 inches (171 mm) deep. The system weight shall be 12.5 lbs (5.7 kg). The PA system shall display UL, CSA and CE agency markings. The PA system shall be the Galaxy Audio CORE PA5X140.

Specifications subject to change without notice.

**GALAXY AUDIO**

601 E. Pawnee Wichita, KS 67211 316.263.2852 FAX 316.263.0642 www.galaxyaudio.com

Distributed outside the United States and Canada by **E and E Exports, Inc.** 17922 Sky Park Circle, Suite P, Irvine, CA 92714
949.440.0760 FAX 949.440.0766

Distributed in Canada by **A.C. Simmonds & Sons Limited** 580 Granite Court, Pickering, Ontario, Canada L1W 3Z4
905.839.8041 FAX 905.839.2667